

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 101700

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31, T27-3

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5048)

Set post cor. to secs. 36 and 31, being the closing cor. to
Tps. 27 S Ranges 3 & 4 West, from which
A Laurel, 14" dia. bears S.35°W., 22 lks. dist.
A Laurel, 10" dia. bears S.31°E., 17 lks. dist.
A Laurel, 15" dia. bears N.40°E., 21 lks. dist.
A Laurel, 14" dia. bears N.23°W., 18 lks. dist.

Resurvey Exteriors, by W.H. Byars, Contract #376 dated
January 22, 1881 (DCSO Records, Volume 12 Page 5082)

Sec. cor., Set new post, witness trees all standing (as
described above)

Doug. Co. Surveyors Office - J. Byron; M. Godfrey; C. Putnam
July 14, 1961 - C.S. File 49/67-10

Found - All orig. BTs. The SW and NW orig. BTs show good
scribing. All check record.
Stake at corner.
New BTs- 20" (orig) Laurel bears N.22°W., 12.5 ft. scribed
S 36 T27S R4W CS BT.
32" (orig) Laurel bears N.50°E., 13.0 ft. scribed
S 31 T27S R3W CS BT.

Doug. Co. Surveyors Office - Milo Godfrey; Wm. Stoffel;
Darby; Stone; Halterman - October 1963 - C.S. File 53/33-21

Found - Wooden stake at corner.
20" Laurel, N.22°W., 12.5 ft. scribed S36 T27S R4W
CS BT in 1961.
32" Laurel N.50°E., 13.0 ft. scribed S31 T27S R3W CS
BT in 1961.
Both BTs alive and in good condition. Other two BTs
no longer showing scribe marks.
Drive 3/4" Iron Rod in corner in place of wooden stake.

Doug. Co. Surveyors Office - Randall Smith; Stephen Flause
Sept. 18, 1989 - C.S. File 64/3-4

(CORNER REPORT ONLY, NO NEW MONUMENT OR ACCESSORIES)
Found - 3/4" dia. 1989 BLM brass cap on a 2 1/2" dia. Iron pipe
(Cont. Next Page)

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

protruding 8" above ground. (Unrecorded 1989 survey)
3/4" Iron rod from 1963 Godfrey renewal not seen. Orig. 14" now 22" dia. Madrone with a rotted out center old blaze with possible reverse scribing visible, bears S.37½°W., 15.9 ft. (Orig. record, S.35°W., 14.5 ft.; BLM tag, N.37½°E., 14.5 ft.)
10" now 24" dia. madrone with a previously opened blaze, no scribing visible, bears S.43°E., 12.6 ft. (Orig. record, S.31°E., 11.2 ft., BLM 1989 tags read N.43°W., 13.8 ft.)
15" now 30" dia. madrone with a partially healed upper blaze scribing visible "T27S R3W S3", lower blaze fully healed, bears N.48½°E., 13.9 ft. (Orig. record, N.40°E., 13.9 ft.; 1989 BT tag S.48½°W., 13.9 ft.)
14" now 20" dia. 7 ft. high madrone snag with a partially healed double blaze scribing visible "T27S R4W S36 CS BT" bears N.24½°W., 12.5 ft. (Orig. record, N.23°W., 11.9 ft.; BLM 1989 tag, S.24½°E., no dist.)
1989 BLM BT, a 7" dia. D. Fir with a single blaze, scribing visible "T27S R4W S36 SC BT" bears N.41½°W., 24.8 ft. (agrees with BLM 1989 BT tag.)
5" dia. D. Fir double blazed, marks visible "X BT" bears N.59°E., 16.1 ft. (1989 BLM BT tag N.59°E., 16.1 ft.)
2½" dia. brass cap on a 1½" dia. Iron pipe protruding 14" above ground, mkd. "County Surveyors Office T27S S36 R4W S1 S6 CC T28S 1961" bears N.87½°W., 52.5 ft. (Rec. 52.0 ft.)

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed July 1989/May 1990 - (DCS0 records Vol. 50 Page(s) 18830-31)

The standard cor. of Tps. 27 S., Rs. 3 and 4 W., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, from which the remains of the original bearing trees:
A madrone, 32 ins. diam., bears N. 48½° E., 21 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. 10° E.)
A madrone, 25 ins. diam., bears S. 43° E., 21 lks. dist., with healed blaze. (Record, S. 31° E., 17 lks.)
A madrone, 22 ins. diam., bears S. 37½° W., 25 lks. dist., with healed blaze. (Record, S. 35° W., 22 lks.)
(Cont. Next Page)

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 101700

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31, T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A madrone stump, 20 ins. diam., bears N. 24½° W., 19 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. 23° W., 18 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over iron rod, with brass cap mkd.

| | | |
|-------------|--------|-------------|
| | SC | |
| | T 27 S | |
| R 4 W | | R 3 W |
| <u>S 36</u> | | <u>S 31</u> |
| 1989 | | |

from which new bearing trees

A fir, 5 ins. diam., bears N. 59° E., 24 lks. dist., mkd. X BT.

A fir, 7 ins. diam., bears N. 41½° W., 37½ lks. dist., mkd. T27S R4W S36 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Found OK by T. Baker, May 2001 - M138-15