

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5595-6)  
-----  
Set cedar stake, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S6 on N., & 7 on S face, from which:  
A cedar, 10" dia., bears N.37°W., 78 lks., mkd: 1/4 S6 BT.  
A laurel, 18" dia., bears S.28°E., 21 lks., mkd: 1/4 S7 BT.

John Markham - For: J.G. Loewen Logging Co. - Feb. 19, 1957 - C.S. File 42/247-1  
-----  
Point for corner determined by OBT: A 20" La. bears S.28°E., 13.9 ft. - found scribe OBT.  
Cedar BT completely gone.  
At the corner point set 5/8"x40" iron bolt with nut on top, 24" in ground, from which  
A 10" cedar bears N.76°E., 19.0 ft. mkd: 1/4 S6 BT  
A 14" la. bears S.38°E., 80.0 ft. mkd: 1/4 S7 BT.  
Logging road bears West 800 ft. more or less, north 330 ft. more or less, & east 240 ft. more or less.

Ted Baker - For: Seneca Jones Timber Co. - May 2001 - M138-15  
-----  
Found - 3/4" iron bolt & nut.  
12" Cedar, N.76°E., 18.1' (scar vis)  
22" Madrone S.28°E., 13.9' (no marks)  
24" Madrone (Blowdown) S.38°E., 80.0' (scar vis)  
New BTs- 10" Fir, S.10°E., 42.4'  
All new BTs are scribed & painted red, distances to BTs are center measure.