

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5572-73)

Intersect S. bdy. of T28S R3W, 11.31 chs. W. of N. ¼ Cor. Sec. 5, T29S R3W.
Set Fir stake 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 31 and 32, marked C C T28S R3W on N.; S31 on W.; and S32 on E. face, with 5 grooves on E. and 1 groove on W. face, from which
A Fir 15" dia., N.9°E., 64 lks. dist. mkd T28S R3W S32 BT.
A Fir 10" dia., N.32°W., 80 lks. dist. mkd T28S R3W S31 BT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Stone; John Powell, crew - July 10/20, 1962 - C.S. File 52/126-8

Found - Orig. 10" now 18" Fir N.32°W., 50.8 ft., not 52.8 ft. (May have been measured as slope dist.)
Set Brass cap at cor. mkd: County Surveyors Office
T 28 S R 3 W
S 31 | S 32
T29S
1962

Corner is at base of 48" Cedar snag.

Douglas Co. Surveyors Office - R.B. Kimberling; F.C. Silagy, crew - Jan. 5, 1978 - C.S. File 59/46-64

Found - 1962 DCSO brass cap on a 1" I.P., 12" above ground.
A 15" now 34" D.Fir bears N.9°E., 42.2 ft. with a well healed double blaze.
A 10" now 18" D.Fir bears N.32°W., 50.8 ft. (Rec. 52.8 ft.) with visible scribing "8 S R 3 W" in a chopped open partially healed blaze.

No new monument set. Stamped "CC" on cap to read:
County Surveyors Office

T 28 S R 3 W
C C
S 31 | S 32
1962

No new accessories.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16876-77)