

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5569)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 29, 30, 31, & 32, marked T28S S 29 on NE, R3W S 32 on SE, S 31 on SW, S 30 on NW faces, with 5 notches on E & 1 notch on S edges; from which
A fir, 8" dia., bears N.1°E., 9 lks., mkd: T28S R3W S29 BT.
A laurel, 5" dia., bears S.36°E., 33 lks., mkd: T28S R3W S32 BT.
A fir, 12" dia., bears S.53°W., 26 lks., mkd: T28S R3W S31 BT.
A maple, 5" dia., bears N.35°W., 29 lks., mkd: T28S R3W S30 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July 1962 - C.S. File 52/126-12

Found - Orig. 8", now 8" R.Fir N.1°E., 5.9 ft. We open & find good scribing. We use this BT to locate position of corner. We find other Orig. BTs thus:
14" R.Fir S.42°E., 19.5 ft. not S.53°W., 17.2 ft.
Forked 10" maple N.42°W. 16.5 ft not N.35°W. 19.1 ft
5" dead Laurel shows good scribing S.29°W., 23.7 ft. not S.36°E., 21.8 ft.
Set Brass cap at cor. mkd: COUNTY SURVEYORS S30|S29 T28S R3W
OFFICE 1962 S31|S32
New BTs- 6" Laurel bears S.43°W., 16.7 ft. scribed S31 T28S R3W CS BT.
10" Maple N.48°W. 16.5 ft scribed S30 T28S R3W CS BT

Glen Baughman - For: Sun Studs - July 1971 - M43-19

Found - Brass cap
8" D.Fir N.1°E., 5.9'
14" D.Fir S.42°E., 19.5'
6" Madrone bears S.43°W., 16.8'
10" Maple bears N.48°W., 16.4'
10" Maple N.42°W., 16.6'

Dan Saily- For: Lone Rock - 9/2023 - C.S. File 65/113-16

Found - 1962 Douglas County brass cap and pipe
8" D.Fir snag found at M43-19 rec N.1°E., 5.9'
healed face & Oregon State Board of Forestry tag.
Continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

16" D.Fir fd at M43-19 rec. S.42°E., 19.6 healed face and BLM tag.
8" Madrone fd at M43-19 rec. S.43°W., 16.8' rotten face and BLM tag.
12" Maple fd at M43-19 rec. N.48°W., 16.4' healed face and BLM tag.
16" Maple found at M43-19 rec. N.42°W., 16.6' no tag or face evident.

Note - FD 1962 Douglas County Surveyor Office brass cap on pipe as per 1971 Baughman survey M43-19 top of corner monument is 1.5 ft above ground level. Monument lies on steep west facing slope. BTs were checked with a tape and compass. Diameters of BTs were measured using a diameter tape and are shown hereon. An averaged GNSS position was taken using TRIMBLE R12I Receivers using RTK and a locally established base.
(NAD 83 EPOCH 2011)
Lat: N 43°05'53.76" Long: W 123°05'25.22"
Base of bearing: Baughman 1971 survey M43-19
See also map C.S. File 65/112-4 filed 1/10/2024