

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5577)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 19, 20, 29, & 30, marked T28S S 20 on NE, R3W S 29 on SE, S 30 on SW, S 19 on NW faces, with 2 notches on S & 5 notches on E edge; from which

A laurel, 12" dia., bears N.6°E., 110 lks., mkd: T28S R3W S20 BT.

A fir, 8" dia. bears S.13°E., 46 lks. mkd: T28S R3W S29 BT

A fir, 8" dia. bears S.47°W. 150 lks. mkd: T28S R3W S30 BT

A fir, 12" dia. bears N.43°W. 34 lks. mkd: T28S R3W S19 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-41

Found - All orig. BTs. All show good scars & check record. The NE BT shows scribe marks.

Set Brass cap at cor. mkd: COUNTY SURVEYORS S19|S20 T28S R3W
OFFICE 1962 S30|S29

No new Bearing trees.