TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17 & 18 only, South

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5530)

Set cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 17, 18, 19, & 20, marked T28S S 17 on NE, R3W S 20 on SE, S 19 on SW, S 18 on NW faces, with 5 notches on E & 3 notches on S edges; from which

A fir, 8" dia., bears N.60°E., 9 lks. mkd: T28S R3W S17 BT
A fir, 36" dia. bears S.20°E. 26 lks. mkd: T28S R3W S20 BT
A fir, 10" dia. bears S.30°W. 27 lks. mkd: T28S R3W S19 BT
A fir, 12" dia. bears N.60°W., 9 lks. mkd: T28S R3W S18 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - D. McFarland - John Powell - March 1962 - C.S. File 49/67-38

Found - 36" now 44" R.Fir S.20°E., 17.2 ft. shows fair bark scribing.
Orig. 10" now 20" fir S.30°W. 17.8 ft shows old scar
Orig. 12" now 14" W.Fir N.60°W., 5.9 ft. shows bark scribing.
We also find stump of orig. NE BT.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962
S18|S17 T28S R3W

New BT - 21" W.Fir bears N.59½°E., 22.0 ft. scribed S17 T28S R3W CS BT.

Rescribe- Now 14" W.Fir N.60°W., 5.9 ft. S18 T28S R3W CS BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed May/June 2006 - (DCSO records Vol. 56 Page(s) 22271 & T28-3 2011 plat)

The cor. of secs. 17 and 18 only, remonumented by Byron, Douglas County Surveyors Office, in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A burnt fir snag, 56" dia., bears S.20°E., 17.2 ft., with no marks visible.
A sawed burnt fir stump, 19" dia., bears S.24¼°W., 16.8 ft., with no marks visible. (Record S.30°W.. 15.8 ft.)
A decayed fir stump, size indeterminate, bears N.60°W., 5.9 ft., with no marks visible.

and remains of a bearing tree mkd. by Byron

A decayed fir snag. 6" dia,, bears N.57½°E., 21.5 ft., with a healed blaze.

and new accessories

continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17 & 18 only, South

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A rebar, 30" long, 5/8" dia., driven 30 ins. in the ground for a reference monument, bears N.46°54'26"E., 8.4 ft. with alum. cap mkd. RM T28S R3W S17 8.4 FT TO COR 2006 and an arrow pointing to the corner.
A fir, 8" dia., bears N.9¼°W. 70.0 ft. mkd T28S R3W SIB BT