

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5589)  
-----  
Set cedar stake, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S18 on W and 17 on E face; from which  
    A cedar, 18" dia., bears S.49°E., 12 lks., mkd: 1/4 S17 BT.  
    A cedar, 6" dia., bears N.70°W., 42 lks., mkd: 1/4 S18 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy & Crew  
- March 1962 - C.S. File 49/67-38B  
-----  
Found - Both orig. BTs:  
    Orig. 18" now 18" cedar S.49°E., 7.9 ft. shows good scribing.  
    Orig. 6" now 10" cedar N.70°W., 27.7 ft. shows good scar.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962  
                                    1/4 S18|S17 T28S R3W  
No new BTs.

Fd. Ok by W. Ruppert 10/1981 - M89-20  
Fd. ok R. Brown 11/1993 - M119-11

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed May/June 2006 - (DCSO records Vol. 56 Page(s) 22271 & T28-3 2011 plat)  
-----  
The 1/4 sec. cor. of secs. 17 & 18, remonumented by Byron, Douglas County Surveyors Office, in 1962, monumented with an iron post, 1 1/4" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.  
from which the original bearing trees  
    A cedar, 6" dia., bears S.49°E., 7.9 ft., with a healed blaze.  
    A cedar, 18" dia., bears N.70°W., 27.7 ft., with a healed blaze.