

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The orig. NW BT is gone.
The SE & SW BTs marked in 1957 have been destroyed.
The NW BT marked in 1957, an 18" cedar, now a 20" stump, bears N.39½°W., 64.9 ft.

New BTs- 12" D.Fir bears S.7°E., 5.4 ft. scribed "T28S R3W S17 CS BT"
10" D.Fir bears S.37½°W., 10.4 ft. scribed "T28S R3W S18 CS BT."
7" G.Fir bears N.82½°W., 12.4 ft. scribed T28S R3W S7 CS BT.

Note - This corner is located approx. 75 ft. north of North Myrtle County Rd.
Compass declination setting: 20° East.

FD. Ok by R. Brown, 11/1993 - M119-11

Greg Lang - For: Seneca Jones Timber Co. - July 2001 - M 138-46 and C.S. File 65/37-14D

Found - Byron Brass Cap properly marked. 1957
Fd. accessories according to the 1975 renewal by Langlitz
Set - Aluminum post by the corner.
I set spikes in the following trees:
29" Cedar bears N.35½°E., 29.5 ft. (placed new tag)
21½" D.Fir bears S.11½°E., 5.4 ft.
18" D.Fir bears S.33½°W., 10.4 ft.
14" W.Fir bears N.84¾°W., 12.4 ft. (placed new tag)

Note - Less than 100' N'ly of North Myrtle Rd. just before the current end of pavement.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed May/June 2006 - (DCSO records Vol. 56 Page(s) 22271 & T28-3 2011 plat)

The cor. of secs. 7, 8, 17, & 18, remonumented by Byron, in 1957, rehabilitated by Langlitz, in 1975, and perpetuated by Lang, in 2001, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground w/brass cap (properly) mkd from which the remains of the original BTs
A sawed decayed fir stump, 30" dia., bears S.68¾°E., 25.4 ft., with axe marks visible. (Record S.65°E., 23.8 ft.)
A decayed fir stump, 30" dia., bears S.58°W., 10.6 ft., with axe marks visible.
and bearing tree mkd. by Byron
A cedar, 32" dia., bears N.35¾°E., 29.5 ft., with a healed blaze.
continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing tree mkd. by Langlitz
A fir, 23" dia., bears S.11°E., 5.6 ft., with a healed blaze.
A fir, 20" dia., bears S.35½°W., 10.5 ft., with a healed blaze.
A dead fir, 14" diam., bears, N.83¼°W., 12.4 ft. with a healed blaze.
and new bearing tree
A fir, 9" dia., bears N.65°W. 14.7 ft. mkd. T28S R3W S7 BT
Latitude 43°08'28.04"N. Longitude 123°05'25.46"W.
(NAD 1983 (CORS 96))

Fd. as per record by D. Edwards 5/2021 - M179-39