

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5592)

Set cedar stake, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S7 on W., & 8 on E face, from which:

A cedar, 10" dia., bears S.82°W., 12 lks., mkd: ¼ S7 BT.

A hemlock, 12" dia., bears S.21°E., 19 lks., mkd: ¼ S8 BT.

NOT FOUND

Shown as not found on the previous corner renewal index sheet
Could find no record of visit but most likely DCSO in 1960's

Greg Lang - For: Seneca Jones Timber Co. - July 2001 -
M 138-46 and C.S. File 65/37-14C

Found - Orig. Hemlock BT (now 29"), good face, we cut in & fd scribing approx. 6" from the core of the tree.
Orig. Cedar not found.

Set - 5/8"x36" iron rod with a 2½" alum. cap. This monument was set N.21°W., 12.54 ft. or 19 lks. (the orig. rec. bearing & dist.) from the 1910 Hemlock described above. Also set an alum. post alongside the corner.

15½" Hemlock bears N.35½°E., 51.0 ft. scribed "¼ S8" "BT"

15½" Hemlock bears S.48¾°E., 46.4 ft. scribed "¼ S8" "BT"

9½" D.Fir bears S.60¼°W. 33.5 ft scribed "¼ S7" "BT"

9½" D.Fir bears N.17°W., 44.5 ft scribed "¼ S7" "BT"

Set spike in the base of the trees & placed new tags.

Note - Corner is on an easterly slope.