

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5596-97)

Intersect 17 lks. E. of cor. secs. 31 and 32.
Set Cedar stake 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 5 and 6, marked CC T28S R3W on S.; S5 on E.; and S6 on W. face, with 5 grooves on E. and 1 groove on W. face, from which
 A Fir 12" dia., bears S.70°E., 20 lks. dist. mkd. T28S R3W S5 BT.
 A Laurel 18" dia., bears S.40°W., 20 lks. dist. mkd. T28S R3W S6 BT.

Survey by John H. Markham, Jr. - For: J.G. Loewen Logging Co. - Feb. 19, 1957 - C.S. File 42/247-2

Found - 14" Fir bears S.70°E., 13.2 ft., found scribe.
 20" Laurel windfall, bears S.65°W., 18.0 ft., found scribe.
At corner point, Set 1½" x 20" steel shaft 14" in ground, from which
 20" Laurel bears S.25°W., 32.0 ft. mkd. S6 BT.
 30" Cedar bears N.8°E., 27.2 ft. mkd. S32 BT.
Sec. corner to secs. 31 and 32, bears West 11.2 ft.
Main top bears West 120.0 ft.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18828)

The closing cor. of secs. 5 and 6, T. 28 S., R. 3 W., perpetuated and recorded by Markham Jr., Registered Engineer No. 2880, in 1957, from original evidence no longer in existence, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Markham:
 A burned cedar stump, 20 ins. diam., bears N. 10° E., 40 lks. dist., no marks visible.
 A sawed madrone stump, 22 ins. diam., bears S. 29° W., 51 lks. dist., no marks visible on burnt out center.
At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION CC for Secs. 5 & 6 only, T28-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 27 S R 3 W
 S 32
S 6 | S 5
 C C
T28 S R 3 W
 1990

from which new bearing trees
 A white fir, 15 ins. diam., bears S. 9¼° E., 37 lks.
 dist., mkd. T28S R3W S5 CC BT.
 A fir, 5 ins. diam., bears S. 41° W., 45 lks. dist.,
 mkd. X BT.
Deposit a white "DEEP-1" magnetic marker at the base and an
iron pipe alongside the stainless steel post.

Found OK by T. Baker, May 2001 - M138-15