

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32, T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, contract #454, dated June 19, 1882
(DCSO records Vol. 12 Page(s) 4975)

Set Laurel post 3 ft. long, 3" sq., for 1/4 sec.cor. mkd. S C
1/4 S on N. face, from which

A Laurel 18" dia., bears S.50°E., 126 lks. dist. mkd. S C
1/4 S BT.

A Laurel 20" dia., bears N.20°E., 21 lks. dist. mkd. S C
1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John
Powell & Bill Stoffel, crew - Sept. 1962 - C.S. 52/126-45

Found - Orig. 18" now 22" Laurel S.50°E., 7.9 ft. not 83.2
ft., shows good scribing "1/4". (We find SE. BT
dist. should be 12 lks. not 126 lks. as this area
has a great number of old Laurel and Fir trees
that would have been close to corner had the
dist. been as recorded.)

Orig. 20" now 24" Laurel N.20°E., 13.9 ft. We open
but old face rotted, no scribing found.

Set brass cap at cor. mkd. County Surveyors Office

T 27 S R 3 W
South 1/4 S 32
T28S
1962

New BTs- 7" Fir bears N.27°E., 23.4 ft. scribed S1/4 S32 CSBT
28" Laurel bears N.52°W., 24.5 ft. scribed S1/4 S32 CS
BT.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed
July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18827-28)

The standard 1/4 sec. cor. of sec. 32, perpetuated and recorded
by Byron in 1962, monumented with an iron post, 1 1/4 ins.
diam., firmly set, projecting 15 ins. above ground, with
brass cap mkd. in 1962

from which the remains of the original bearing trees

A dead madrone, 23 ins. diam., bears N. 20° E., 21 lks.
dist., no marks visible on an opened, partially
healed double blaze.

A root hole, bears S. 50° E., 12 lks. dist., with
rotted remains of madrone alongside, no marks visible.
(Record, 126 lks.)

and the remains of a bearing tree mkd. by Byron

A dead madrone, 26 ins. diam., bears N. 50° W., 37 lks.
dist., with scribe marks 1/4 S 32 visible on partially
healed blaze.

(Cont. Next Page)

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 239700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec 32 only, T27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees

A fir, 13 ins. diam., bears N. 71° E., 3 lks. dist.,
mkd. ¼ S 32 SC BT.

A fir, 10 ins. diam., bears N. 15 3/4° W., 10 lks. dist.,
mkd. X BT.