

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5590-1)</p> <p>-----</p> <p>Set hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S8 on N &amp; 17 on S face; from which A hemlock, 8" dia., bears N.9°E., 10 lks., mkd: 1/4 S8 BT. A cedar, 14" dia., bears S.30°E., 30 lks., mkd: 1/4 S17 BT.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July 1962 - C.S. File 52/126-13</p> <p>-----</p> <p>Found - 8" now 13" hemlock N.9°E., 6.6 ft. We open &amp; find good scribing. Orig. SE BT not found. Set - Brass cap at cor. mkd: County Surveyors 1/4 S 8 T28S R3W Office 1962 S 17 New BT - 7" Hemlock bears S.58°E. 31.3 ft scribed 1/4 S17 CS BT</p>
<p>Greg Lang - For: Seneca Jones Timber Co. - July 2001 - M 138-46 and C.S. File 65/37-14E</p> <p>-----</p> <p>Found - Brass cap set by Byron, loose &amp; leaning, but still firmly in the ground at the base. We straighten &amp; tighten; build rock mound. Orig. NE BT (now 14" Hemlock) bears N.13 1/4°E. 5.6 ft Set spike in the base of the tree &amp; placed new tag Also fd. Byron's SE BT down, root hole matches cap position. Set - Also set an alum. post alongside the corner. 11" W.Fir bears S.81 1/4°E. 14.8 ft scribed "1/4 S17" "BT" 8" Hemlock bears S.76°W. 32.2 ft scribed "1/4 S17" "BT" 15" Hemlock bears N.58°W. 24.8 ft scribed "1/4 S8" "BT" <u>Set spike in the base of the trees &amp; placed new tag.</u> Note - <u>Corner lies at the foot of a NW'ly slope &amp; approx. 30' West of a small creek.</u></p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Sept. 2011 - (DCSO records BLM Plat T28-3W 2012-1 &amp; Vol. 58 Pages 22949)</p> <p>-----</p> <p>The 1/4 sec. cor. of secs. 8 &amp; 17, perpetuated by Byron in 1962, subsequently perpetuated by Lang in 2001, monumented with an iron post, 1 1/4" dia., firmly set, projecting 12" above the collar of stone, with brass cap (properly) mkd. from which the remains of an orig. BT A hemlock snag, 17" dia., bears N.9°E., 6.6 ft. with a healed blaze. continued next page</p>

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and BTs by Lang

A fir, 15" dia., bears S.80 $\frac{3}{4}$ °E., 15.1 ft. with a healed double blaze.

A hemlock, 11" dia., bears S.75 $\frac{3}{4}$ °W., 32.1 ft., with scribe marks  $\frac{1}{4}$  S17 on upper and BT visible on lower partially healed double blaze.

A hemlock, 19" dia., bears N.57 $\frac{3}{4}$ °W., 24.5 ft. with scribe marks  $\frac{1}{4}$  S8 on upper & BT visible on lower partially healed blazes.

Corner is located 30 ft. E of a creek, 2 ft. wide course N.40°W.