

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5593)

Set cedar stake, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S5 on N., & 8 on S face, from which:
A maple, 10" dia., bears N.10°W., 3 lks., mkd: 1/4 S5 BT.
A cedar, 5" dia., bears S.12°W., 40 lks., mkd: 1/4 S8 BT.

Claude Kerr - Sept. 1956 - C.S. File 42/91

Found - Orig. BT, now an 18" maple bearing N.10°W., 3 lks. I chopped in the old face & found the old marking and then rescribed the outside with 1/4 S5.
Set - 3"x4"x4' cedar stake for corner.
New BT - 10" W.Fir bearing S.17°W., for 19.4 ft. & scribed S 1/4 8 BT on the face.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July 1962 - C.S. File 52/126-15

Found - BTs & stake at corner as recorded by Kerr.
Set Brass cap at cor. mkd: COUNTY SURVEYORS 1/4 S 5 T28S R3W
OFFICE 1962 S 8

Greg Lang - For: Seneca Jones Timber Co. - July 2001 - M 138-46 and C.S. File 65/37-14 A

Found - Brass cap set by Byron in 1962
Orig. 1910 Maple now 21" dia., bears N.10°W., 3 lks
Set spike in the base of the tree & placed new tag
Kerr's 1956 W.Fir now 20" dia., bears S.17 1/4°W., 18.6 ft. (We set a spike in this tree, but scratched our information on the existing BT tag
Also fd. a metal "T" post at the corner.
New - 7" Hemlock bears N.88 3/4°E. 19.0' scribed "1/4 S5" "BT"
10" Hemlock bears S.70 1/2°E. 24.3' scribed "1/4 S8" "BT"
6" Hemlock bears N.76 3/4°W. 27.0' scribed "1/4 S5" "BT"
Set spike in the base of the trees & placed new tag.
Note - Corner lies on westerly slope less than 100' East of a drainage; also at the S'ly edge of logged unit