

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T29-3

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6326)

Set Laurel post for cor. to secs. 4, 5, 32 and 33, from which
A Fir 14" dia., bears N.20°E., 22 lks.
A Fir 46" dia., bears S.50°E., 37 lks.
A Fir 44" dia., bears S.70°W., 33 lks.
A Fir 18" dia., bears N.30°W., 16 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5562)

Cor. secs. 4, 5, 32 and 33, which is a stake marked and witnessed as described by the surveyor general.
I destroy markings on stake and bearing trees referring to secs. 32 and 33.

Survey by Warren D. Hootman - For: Mr. J.P. Heath - Sept. 21, 1960 (Filed Jan. 13, 1961) - C.S. File 51/164 and M 20-5

Find two Firs of approx. size which match for bearing and distance which I believe to be the original BTs.
I set a 3/4" Iron pipe from the 2 BTs at the distance and bearing called for by the government notes and witness the corner as follows:
Madrone 4" DBH bears West 5.2 ft.
Madrone 16" DBH bears S.45°E., 13.5 ft.

Survey by Bruce A. Shaner, LS #430 - For; Longview Fibre - Sept. 25, 1978 - M 73-52

Found 3/4" Iron pipe.
I Set a brass cap alongside mkd. "5, 4, T29S R3W 1978", from which
16" now 20" Madrone BT scribes visible bears S.45°E., 13.5 ft.
10" D.Fir, I scribe "T29S R3W S5 BT" bears S.33°W., 54.4 ft.
46" D.Fir, Orig. BT, snag, face chopped out, bears S.50°E., 24.4 ft.
44" D.Fir, Orig. BT, blowdown, bears S.70°W., 21.8 ft.
36" D.Fir, Orig. BT, blowdown, bears N.20°E., 14.5 ft.
4" Madrone BT, bears West, 5.2 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T29-3

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #997, surveyed Oct 1979/April 1980 (DCSO records Vol. 43 Page(s) 16875)

The Sec. cor., perpetuated and recorded by Hootman in 1960, further perpetuated and recorded by Shaner in 1978, monumented with an iron post 1¼" dia., firmly set, projecting 3" above ground with brass cap mkd. by Shaner, from which the remains of the original bearing trees:

A Fir stump 38" dia., bears S.50°E., 37 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Hootman:

A Madrone stump 17" dia., bears S.48°E., 21 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A Madrone 4" dia., bears N.76¼°W., 7 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and new bearing trees:

A Fir 4" dia., bears S.35°E., 119 lks. dist. mkd. X BT.

A Fir 9" dia., bears S.46°W., 157 lks. dist., mkd. T29S R3W S5 BT.

Rob Ward - For: Seneca Jones Timber Co. - Jan. 2003 - M141-30

Found - BLM brass cap dated 1981
38"x' D.Fir stump bears S.50°E. 24,4', burned face
17"x5' Madrone stump with metal cap bears S.48°E., 13.9' -partially healed face.
10"x5' D.Fir stump with metal top bears S.46°W., 103.6' - healed face

Rec. 4" madrone N.76¼°W., now stump sprout no marks.

Rec. 4' D.Fir S.35¼°E., now burned stub

New - 8" D.Fir bears S.70¼°W 9.51 blazed, scribed "T29S R3W S5 BT"

6" D.Fir bears S.36½°E., 4.7' blazed, scribed "T29S R3W S4 BT"

Also found 3/4" iron pipe next to brass cap.