

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5568)

-----  
Set cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 28, 29, 32, & 33, marked T28S S 28 on NE, R3W S 33 on SE, S 32 on SW, S 29 on NW faces, with 4 notches on E & 1 notch on S face; from which

A cedar, 18" dia., bears N.87°E., 5 lks., mkd: T28S R3W S28 BT.

A cedar, 24" dia., bears S.11°E., 16 lks., mkd: T28S R3W S33 BT.

A fir, 24" dia., bears S.42°W., 70 lks., mkd: T28S R3W S29 BT.

A cedar, 12" dia., bears N.23°W., 34 lks., marked T28S R3W S29 BT. (Typed from line notes on the internet. Our records left this BT out of our typed copy of the line notes - DCSO JC 3/18/2009)

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Mike Stone - July 1962 - C.S. File 52/126-5

-----  
Found - Scribed post at corner & all BTs as recorded.  
14" Cedar bears N.31°W., 23.6 ft. shows old scribing but this is not of record. (3/18/2009 DCSO JC- I researched the orig. line notes & fd record of an orig. NW BT that wasn't typed before - see above)

Set Brass cap at cor. mkd: COUNTY SURVEYORS S29|S28 T28S R3W  
OFFICE 1962 S32|S33