

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5573)

Set granite stone 6x8x14", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A cedar, 14" dia., bears N.45°W., 2 lks., mkd: ¼ S29 BT.
 A fir, 6" dia., bears N.37°E., 34 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July/Aug. 1962 - C.S. File 52/126-11

Found - Stone at corner as recorded.
 Orig. 14" cedar now 25" N.45°W., 1.3 ft. shows scribing.
 Orig. NE BT down shows scar.
New BTs- 5" R.Fir bears S.69°E., 10.3 ft scribed ¼ S28 CS BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - John Heritage - V. Perron - March 12, 1970 - C.S. File 52/126-151

Found - Corner stone in place, broken, "4" on lager piece.
 Orig. 14" now 26" cedar N.45°W., 1.3 ft. now sawed stump, scribe on log.
 1962 BT buried under logs.
Set - 1" IP & brass cap mkd: COUNTY SURVEYORS OFFICE 1970
 T28S ¼ S29|S28 R3W
 Set 6.0 ft. steel fence post 1.0 ft. south of cap.
New BTs- 6" D.Fir S.67°W., 13.7 ft. mkd: ¼ S29 CS BT.
 6" Hemlock N.35°W., 11.8 ft. mkd: ¼ S29 CS BT.
This corner lies in cutoff unit approx. 300 ft. West of road.