

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5573-4)

Set granite stone 6x10x15", 10" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 4 notches on E & 2 notches on S face, from which

- A maple, 8" dia., bears N.89°E., 26 lks., mkd: T28S R3W S21 BT.
- A maple, 6" dia., bears S.17°E., 26 lks., mkd: T28S R3W S28 BT.
- A maple, 7" dia., bears S.20°W., 20 lks., mkd: T28S R3W S29 BT.
- A dogwood, 5" dia., bears N.18°W., 36 lks., mkd: T28S R3W S20 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July 1962 - C.S. File 52/126-10

Found - Orig. 6" or 7" maple BT, down & out of position, shows good reverse scribing. Corner is on steep south slope about 75 ft. N of bottom of draw. This BT could be either SW or SE Orig. BT. I find maple stump hole that checks for SE BT location. We also find yellow tag on 5" fir North 12.0 ft. It is marked about 16 years ago.

Set Brass cap at cor. mkd: COUNTY SURVEYORS S20|S21 T28S R3W
OFFICE 1962 S29|S28

- New BTs-
- 11" R.Fir bears N.22°E., 30.9 ft. scribed S21 T28S R3W CS BT.
 - 21" R.Fir bears N.55°W., 70.5 ft. scribed S20 T28S R3W CS BT.
 - 11" Maple bears S.5°E., 43.7 ft. scribed S28 T28S R3W CS BT.
 - 9" Yewood bears South 49.0 ft. scribed S29 CS BT.

Note - Corner stone not found.