TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5576)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S 20 on W & 21 on E face; from which
A fir, 8" dia., bears S.17°E., 23 lks., mkd: ¼ S21 BT.
A fir, 7" dia., bears S.15°W., 25 lks., mkd: ¼ S20 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-22

Found - Both Orig. BTs
Orig. 7" now 13" R.Fir bears S.57°W., 16.5 ft. not S.15°W., 16.5 ft. We open this BT & find good scribing.
Orig. 8" now 18" R.Fir bears S.20°E., 15.2 ft. not S.17°E., shows good scar.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962
¼ S20|S21 T28S R3W

Note - Corner is about 100 ft. East of draw & on West slope of ridge & 100 ft. West of top of ridge.