

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5583)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 8, 9, 16, & 17, marked T28S S 9 on NE, R3W S 16 on SE, S 17 on SW, S 8 on NW faces, with 4 notches on S & E edges; from which
 A hemlock, 5" dia., bears N.63°E., 45 lks., mkd: T28S R3W S9 BT.
 A cedar, 24" dia., bears S.67°E., 51 lks., mkd: T28S R3W S16 BT.
 A hemlock, 4" dia., bears S.34°W., 35 lks., mkd: T28S R3W S17 BT.
 A cedar, 30" dia., bears N.37°W., 65 lks., mkd: T28S R3W S8 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Oct. 1957 - C.S. File 49/22-5

Found - Orig. 30" Cedar now 36", open face scribed "T28S R3W S8 BT" N.37°W., 42.9 ft.
 Orig. 5" hemlock now 10" open face scribed "R3W S9" N.63°E., 29.7 ft.
 I also find cedar stump that checks size, bearing & distance for orig. SE BT broken off near ground. No scribing found.
Set brass cap at corner mkd T28S R3W S 8|S 9 County Surveyors S17|S16 Office 1957
New BTs- 18" hemlock bears S.5°E., 13.6 ft. scribed S16 T28S R3W CS BT.
 13" hemlock bears S.82½°W., 44.4 ft. scribed S17 T28S R3W CS BT.
 36" cedar (orig.) N.38°W., 44.2 ft. I rescribe, S8 T28S R3W CS BT.
 The NE orig. BT is in good condition. I find the bearing & distance should be N65°W., 29.7 ft.

Douglas Co. Surveyors Office - John Powell & crew - 12/1966 - C.S. File 52/126-147

Found - County Surveyors brass cap mkd 1957.
 18" hemlock now 19" S.5°E., 13.6 ft scribing visible
 36" cedar N.38°W., 44.2 ft. scribing visible.
 10" hemlock N.65°E., 29.3 ft.
 13" hemlock now down S.82½°W., 44.4 ft.
New BT - 7" hemlock S.85°W., 36.7 ft. scribed T28S R3W S17 CS BT.

Cont.

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

David Edwards - For: Seneca Jones Timber Co. - 10/2000 -
C.S. File 65/29-10

Found - DCSO brass cap.
40" dia., Cedar (1957 BT) bears N.38°W., 44.2 ft.
6" dia. Hemlock scribed "S9 BT" bears N.34°E., 10.40
ft.
New - 5" dia. Hemlock scribed "S16 BT" bears S.71°E., 15.0
ft.
6" dia. Hemlock scribed "S17 BT" bears S.39°W., 7.25
ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2500, Surveyed Aug./Sept. 2011 -
(DCSO records BLM Plat T28-3W 2012-1 & Vol. 58 Pages 22949)

The cor. of secs. 8, 9, 16, & 17, perpetuated by Byron in
1957 subsequently perpetuated by the DCSO in 1966, and
further perpetuated by Edwards in 2000, monumented with an
iron post, 1¼" dia., firmly set, projecting 11" above ground,
with brass cap (properly) mkd.
from which the remains of orig. BTs

A decayed hemlock root crown, size indeterminate, bears
N.63°E., 29.7 ft. with no marks visible.

A cedar, 40" dia., bears N.39¼°W., 42.9 ft. with
fragmentary scribe marks visible on partially healed
blaze (Rec. N.37°W., rescribed by Byron)

and the remains of a BT mkd. by Byron

A roothole bears S.5°E., 13.2 ft. downhill of which is a
fallen, decayed, sawed hemlock trunk segment, size
indeterminate, with no marks visible.

and BTs mkd by Edwards

A hemlock, 8" dia., bears N.38°E., 10.4 ft., with scribe
marks S9 BT visible on a partially healed blaze.

A hemlock, 6" dia., bears S.69¼°E., 15.1 ft. with scribe
marks S16 BT visible on a partially healed blaze.

A hemlock, 8" dia., bears S.37½°W., 7.2 ft. with
fragmentary scribe marks visible on a partially healed
blaze.

Corner is located 40 ft. N of a gravel road, 13 ft. wide,
bears N.65°W., and S.65°E., 90 ft. E of the same road, 13 ft.
wide, bears N.50°W., and S.60°E., in a curve.

(NAD 1983 (CORS 96))

Latitude 43°08'27.63"N Longitude 123°04'15.40"W