TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5585)

Set laurel stake, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 8, & 9, marked T28S S 4 on NE, R3W S 9 on SE, S 8 on SW, S 5 on NW faces, with 4 notches on E & 5 notches on S edge; from which

A laurel, 12" dia., bears N.22°E., 71 lks., mkd: T28S R3W S4 BT.
A fir, 40" dia., bears S.17°E., 44 lks., mkd: T28S R3W S9 BT.
A cedar, 60" dia., bears S.22°W., 69 lks., mkd: T28S R3W S8 BT.
A fir, 5" dia., bears N.51°W., 107 lks., mkd: T28S R3W S5 BT.

Claude Kerr - Sept. 1956 - C.S. File 42/91

Found only one orig. BT, now a 46" D.Fir, bearing S.17°E., for 44 lks. I chopped in and found old scribe marks. I rescribed this tree with S9 BT and used it to reset the corner stake.
Set a 4"x4"x4' cedar stake marked S4, S5, S8 & S9
Marked one new BT:

A 42" D.Fir bearing N.39°E., 50.7 ft. marked S4BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July 1962 - C.S. File 52/126-14

Found - Corner scribed stake & orig. SE BT & new BT, all as recorded by Kerr, 1946. BTs are now down.
Set brass cap alongside corner stake & mkd: S 5|S 4 T28S R3W County Surveyors Office 1962 S 8|S 9
New BTs- 14" R.Fir bears N.1½°W., 47.3 ft. scribed S5 T28S R3W CS BT.
6" R.Fir bears S.8°W., 46.3 ft. scribed S8 CS BT.
7" R.Fir bears S.81°E., 39.1 ft. scribed S9 CS BT.
5" R.Fir bears N.68°E., 32.6 ft. scribed S4 CS BT.

Corey Woodruff - 6/2007 - M153-69

Found - County Surveyor BCIP set by Byron
24" R.Fir bears S.8°W., 46.3'
26" R.Fir bears S.81°E., 39.1'
28" R.Fir bears N.68°E., 32.6'
New - 13" Fir bears N.54°W., 11.8'