

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5588)

Set granite stone 6x10x14", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which
A hemlock, 18" dia., bears N.66°E., 27 lks., mkd: 1/4 S4 BT.
A fir, 30" dia., bears N.45°W., 27 lks., mkd: 1/4 S5 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-34

Found - Stump of orig. NE BT & orig. 30" now 36" fir, previously opened, shows good scribing N.45°W., 17.8 ft.
Also find at corner stone as recorded.
Note - Logging road is about 200 ft. East & small stream about 30 ft. south of 1/4 corner.
Set - Brass cap at cor. & alongside corner stone & mkd: COUNTY SURVEYORS OFFICE, 1962 1/4 S5|S4 T28S R3W
New BT - 7" hemlock bears N.18 1/2°E., 64.9 ft. scribed 1/4 S4 CS BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/9/2021 (Filed 3/21/2023) - C.S. File 67/55-52

Found - Now rotted 30"x3 ft. tall stump, N.45°W., 17.8 ft., open re-healed face, find scribing. 0BT
Set - New monument set at record bearing and dist. From found original NW BT stump. Set A 2 1/2" dia., brass cap on a 32"x1" ID IP set, projecting 8" from ground in a rough mound of stone brass cap mkd: DOUGLAS COUNTY SURVEYORS OFFICE
T28S R3W
1/4
S5|S4
2021
New BTs- A 1" dia., copper drill cap mkd: "SURVEY MARK" set in concrete footing for southerly gate post of steel forest access rd. gate, bears N.6 1/2°E., 71.7 ft.
A 20" dia., D.Fir scribed "1/4S4CS" "BT" on a double blaze; bears N.22°E., 78.8 ft.
An 18" dia., Alder scribed "1/4S5" "CSBT" on a double blaze; bears S.15 1/2°W., 14.9 ft.
OCRS N 120172.110 E 234120.227