TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5568)

Set granite stone 6x8x14", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A cedar, 12" dia., bears S.22°E., 25 lks., mkd: ¼ S33 BT.
A hemlock, 24" dia., bears N.14°E., 14 lks., mkd: ¼ S28 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Mike Stone - July 1962 - C.S. File 52/126-5

Found - Stone at cor. & both BTs as recorded. NE BT now dead
Set Brass cap at cor. & mkd: COUNTY SURVEYORS OFFICE 1962 T28S R3W ¼ S 28 / S 33
New BT - 6" W.Fir bears N.42°E., 14.0 ft scribed ¼ S28 CS BT.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - Teresa Buley - Nov. 23, 1981 - C.S. File 61/29-31

Found - BC protruding 18" above ground, properly mkd. 1962
Orig. 6"x8"x14" stone, now 6"x11"x12" stone with faint "¼" on north face, laying alongside of BC.
Orig. 12" now 17" cedar bears S.22°E., 17.5 ft. (rec. 16.5 ft.) with partially healed blaze w/"S3" visible.
Orig. 24" now a rotten 24" hemlock snag about 20 ft. tall, bears N.14°E., 9.6 ft. (rec. 9.2 ft.) w/no face visible.
6" now 13" fir bears N.42°E., 14-ft w/good scar.1962
New BTs- 7" fir scribed "¼ S28 CS BT" dbl blaze bears N. 50°W., 26.3 ft.
10" fir scribed "¼ S33 CS BT" dbl blaze bears S.77°E., 10.4 ft.
Note - For sketch see C.S. 61/29