

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5587)  
-----  
Set fir stake, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S4 on N & 9 on S face; from which  
A laurel, 16" dia., bears S.10°E., 23 lks., mkd: ¼ S9 BT.  
A chincapin, 8" dia., bears N.16°W., 37 lks., mkd: ¼ S4 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1965 - C.S. File 51/254-25  
-----  
Found - 14" Chinq. N.16°W., 24.4 ft.  
16" Madrone, S.10°E., 16.1 ft.  
New BTs- 36" Fir S.72½°W., 70.1 ft.  
27" Fir N.29½°W., 71.9 ft.  
Note - Proposed road will destroy orig. BTs.

Note - It was determined when the GIS layer was computed that this is not a common corner. DCSO 3/26/2009