

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5564)

Intersect S. bdy. T28S R3W, 447 lks. W. of N. 1/4 Cor., sec. 3. Set granite stone 6 x 10 x 14 ins., 10" in the ground for closing cor. secs. 33 and 34, marked C C on N. face, with 3 grooves on E. and W. faces, from which:

- A Laurel 7" dia., bears N.21°E., 52 lks. dist. mkd. T28S R3W S34 BT.
- A Laurel 7" dia., bears N.36°W., 26 lks. dist. mkd. T28S R3W S33 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Mike Stone, crew - Oct. 1962 - C.S. File 52/126-60

Found both original BTs and stone at corner. NE. BT, shows good scribe marks. NW. BT, shows scars.
Set brass cap alongside cor. stone, mkd:

County Surveyors Office
C C S33 | S34 T28S
T29S R3W

1962

New BT - 24" Cedar bears N.62°W., 27.5 ft. scribed C C S33 T28S R3W CS BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13800)

The closing cor., remonumented and recorded by Byron in 1962, with an iron post, 1" dia., 14" above ground, firmly set, with the original unmarked, granite stone, 6 x 9 x 9 ins., lying alongside, with 1962 brass cap, from which the original bearing trees:

- A Madrone 13" dia., bears N.21°E., 53 lks. dist., with scribe marks visible on an open blaze. (Rec. 52 lks.)
- A Madrone 10" dia., bears N.36°W., 27 lks. dist, no marks visible on an open blaze. (Rec. 26 lks.)