

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5565)  
-----  
Set stone 8x8x12", 8" in the ground for cor. of secs. 21, 22, 27, & 28 mkd with 3 notches on E & 2 notches on S edge, from which  
    A laurel, 10" dia., bears N.75°E., 31 lks., mkd: T28S R3W S22 BT.  
    A fir, 12" dia., bears S.68°E., 77 lks., mkd: T28S R3W S27 BT.  
    A laurel, 6" dia., bears S.72°W., 26 lks., mkd: T28S R3W S28 BT.  
    A laurel, 8" dia., bears N.28°W., 19 lks., mkd: T28S R3W S21 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm Stoffel - Sept. 1962 - C.S. File 52/126-57  
-----  
Found - All Orig. BTs. All check record except Orig. 12", now 30" Fir S.68°E., 44.0 ft., not 50.8 ft, shows good scar.  
    NW BT shows good scribing.  
    Also find Stone at Corner.  
Set - Brass Cap at Cor. Mkd: County Surveyors S21|S22 T28S Office, 1962 S28|S27 R3W  
New BTs- 9" Laurel bears S.35°W. 11.0 ft. scribed S28 T28S R3W CS BT  
    8" Laurel bears N.48°W. 17.8 ft scribed S21 T28S R3W CS BT