TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5567)

Set lava stone 6x10x14", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 36" dia., bears East, 12 lks., mkd: ¼ S22 BT
A fir, 15" dia., bears N.45°W., 36 lks., mkd: ¼ S21 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm Stoffel - Sept. 1962 - C.S. File 52/126-59

Found - Orig. 36" Fir, now 39" East 7.9 ft good bark scribe.
Orig. 15" Fir, now 18" N.45°W., 23.8 ft. good scar.
Also found Lava stone at corner badly chipped & pitted.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962
¼ S 21|S 22 T28S R3W
Orig. trees used: 39" Fir East 9.9 ft.
18" Fir N.45°W., 24.8 ft.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - Teresa Buley - Nov. 25, 1981 - C.S. File 61/29-36

Found - Approx. 6" of the flare, from the bottom of the IP/BC set by DCSO in 1962, buried about 18" in ground.
Orig. 36" now 41" fir stump w/metal cover, bears N.83°E., 9.9 ft. (rec. East) w/bark scribed "¼ S22 BT" visible.
Orig. 15" now 21" fir stump w/metal cover, bears N.45°W., 24.8 ft. w/good scar visible.
Set - At the location of the remaining piece of pipe I set a 1"x30" IP with a BC protruding 6" out of ground & stamped: Douglas Co. Surveyor T28S ¼ S21 S22 R3W 1981.
The fd piece of pipe was re-buried w/the new monument.
New BTs- 10" cedar scribed "¼ S21 CS BT" in dbl. blaze bears S.78°W., 99.8 ft.
5" cedar scribed "¼ S21 CS BT" dbl. blaze bears N.58°W., 30.7 ft.
8" fir scribed "¼ S22 CS BT" in dbl. blaze bears S.32°E., 86.1 ft.
Note - For sketch see C.S. 61/29