

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5544)

Set laurel post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on E & W faces; from which
 A fir, 24" dia., bears S.85°E., 24 lks., mkd: 1/4 S BT.
 A laurel, 8" dia., bears S.55°W., 20 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1 1962 - C.S. File 52/126-18

Found - 9"x9"x6" stone at cor. with 1/4 chiseled on North face.
 We also find now 27" R.Fir bears N.74°E., 23.9' shows good scar.
 Now. 13" R.Fir bears S.83°W., 9.9'. We open this BT & find good scribing, by ring count this tree was scribed about 50 years ago.
 We do find BTs of record.
I believe this cor. was established by Gibb's* 1910 survey, for these reasons:
 1. All scribing on one face.
 2. Rock with chiseled "1/4"
 3. Ring count to old face.
* Per research 3/17/2009 we have no record of Gibb at this corner. DCSO JC

Douglas Co. Surveyors Office - James W. Byron, Deputy - Wm. Stoffel - Oct. 5, 1962 - C.S. File 52/126-62

Found - No Original BTs. We do find 12"x10"x 6" stone with "1/4" chiseled on North face.
 Now 12" Fir bears S.80°W. 9.6 ft. shows good scribing on old face. "1/4" Scribing by ring count checks OK for 1908 survey.
 Now 25" R.Fir N.74°E. 24.5 ft., shows good scar. We do not open
Set - Brass Cap alongside Corner stone & Mark:
 County Surveyors Office, 1962 1/4 S16|S15 T28S R3W
Rescribe - Now 12" R.Fir S.80°W. 9.6 ft. 1/4 S16 CS BT.