

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5544)

Set laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 9, 10, 15, & 16, marked T28S S 10 on NE, R3W S 15 on SE, S 16 on SW, S 9 on NW faces, with 3 notches on E & 4 on S edges; from which

A chinquapin, 8" dia., bears N.20°E., 27 lks., mkd: T28S R3W S10 BT.

A laurel, 7" dia., bears S.5°E., 25 lks., mkd: T28S R3W S15 BT.

A laurel, 12" dia., bears S.70°W., 23 lks., mkd: T28S R3W S16 BT.

A laurel, 7" dia., bears N.76°W., 25 lks., mkd: T28S R3W S9 BT.

Fd. & used on GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page 5584)

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July/Aug 1962 - C.S. File 52/126-19

Found - ¾" IR at corner. *
12" now 20" Laurel S.70°W., 15.2 ft. shows good scribing on old face.

Orig. 7" now 10" Laurel S.5°E., 16.5 ft. shows old scars.

NE & NW BTs not found.

New BTs- 28" R.Fir bears N.33°W., 9.0 ft. scribed S9 T28S R3W CS BT.

OBT rescribed now 20" Laurel, S.70°W., 15.2 ft. S16 CS BT.

14" Laurel bears N.4°E., 40.4 ft. scribed S10 T28S R3W CS BT.

9" R.Fir bears S.14°E., 24.1 ft. scribed S15 T28S R3W CS BT.

* No record of an Iron rod being set 3/17/2009 DCSO JC