

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 33 & 34 only, T27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
- (DCSO records Vol. 12 Page(s) 4976-77)

Set Cedar post, 4 ft. long, 4" sq., firmly in the ground for
standard cor. to secs. 33 and 34, mkd. S C T27S R3W on N.,
S34 on E., and S33 on W. faces with 3 notches on E. and W.
faces, from which

A Laurel 8" dia., bears N.35°E., 89 lks. dist. mkd. S C
T27S R3W S34 BT.

A Cedar 24" dia., bears N.10°W., 77 lks. dist. mkd. T27S
R3W S33 BT.

A Cedar 30" dia., bears S.30°W., 21 lks. dist. mkd. T28S
R3W S4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John
Powell & Wm. Stoffel, crew - Aug/Sept. 1962 - C.S. File 49/28

Found - 3/4" Iron rod at corner.

Orig. 30" now 50" Cedar, S.30°W., 13.9 ft., shows
good old bark scribing.

Orig. 8" now 15" Laurel N.35°E., 58.7 ft., face
rotted.

Also find stump hole for NW. BT.

New BTs- 8" Chinquapin bears N.62°E., 13.7 ft. scribed T27S
R3W S34 CS BT.

14" Laurel bears N.7°W., 50.0 ft. scribed T27S R3W
S33 CS BT.

We also found old bark scribing on now 36" R.Fir "T28S R3W
S3" bears S.27°E., 36.0 ft. I believe this tree was scribed
in 1882 but not recorded.

David Edwards - For: Seneca Jones Timber Co. - Feb. 2013 -
M164-68

Found - 3/4" I.R.

A 15" dia., fir bears N.16°E., 16.2'

A 7" dia., fir bears N.47°W., 34.9'

Set - A 6 ft. steel post 2 ft. north.

S.89°07'57" 46.51 ft from Sec. cor. per M164-68:
Closing corner?

From the Fd iron rod:

A 6" dia., fir bears S.14°E., 26.5'

A 17" dia., fir bears S.35°W., 12.8'

Set - 6 ft. steel post 2 ft. south.