

PRIMARY CORNER DESCRIPTION CC Secs. 21 & 22 North

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5532)

-----

Set Laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 15, 16, 21, & 22, marked T28S S 15 on NE, R3W S 22 on SE, S 21 on SW, S 16 on NW faces, with 3 notches on E & S edges; from which

- A laurel, 10" dia., bears N.55°E., 56 lks., mkd: T28S R3W S15 BT.
- A fir, 24" dia., bears S.45°E., 105 lks., mkd: T28S R3W S22 BT.
- A laurel, 8" dia., bears S.60°W., 70 lks., mkd: T28S R3W S21 BT.
- A fir, 15" dia., bears N.20°W., 70 lks., mkd: T28S R3W S16 BT.

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5566-7)

-----

Page 5566...cor. secs. 15, 16, 21, & 22, which is a stake greatly decayed, bearing trees have been destroyed....

Page 5567

Set fir stake 3 ft. long, 4" sq. 24" in the ground for closing cor. secs. 21 & 22, marked CC T28S R3W on S, S22 on E and S21 on W faces from which

- A fir, 20" dia. bears S.24°E., 44 lks mkd: T28S R3W S22 BT
- A fir, 12" dia. bears S.40°W., 14 lks mkd: T28S R3W S21 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - July/Aug. 1962 - C.S. File 52/126-16

-----

Found - Both BTs as recorded.  
The SW has previously been opened.  
SE BT shows good scar.

Set - Brass cap at cor mkd COUNTY SURVEYORS CC \_\_\_\_\_ T28S R3W  
OFFICE 1962 S21|S22

No new BTs scribed.

Adam DeGroot - For: Seneca Jones Timber Co - July 2017 - M173-46

-----

Found - A 1¼" iron post by Byron in 1962 per C.S. 52/126, projecting 18" above ground, loosely set and leaning south easterly, with a 2½" County Surveyors Office brass cap (properly) mkd.

I reset monument, now projecting 8" above ground, in a 12" stone collar.

From which the original BTs by Gibb in 1910:  
continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 402400

PRIMARY CORNER DESCRIPTION CC Secs. 21 & 22 North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 27" D.Fir high stump bears S.21°45'E., 29.8 ft  
w/healed blaze [S.24°E., 44 lks]  
A 23" D.Fir high stump bears S.40°W., 9.9 ft. I  
reopen blaze and find scribe mks "8S R3W S21 BT"  
[S.40°W., 14 lks]  
New BTs- A 9" D.Fir bears S.42°15'E., 12.5 ft mkd "T28S R3W  
S22 BT"  
A 10" D.Fir bears S.85°W., 22.4 ft mkd "T28S R3W S21  
BT"  
NAD 83 STATION (2011) EPOCH 2010.00 GEODETIC COORDINATES:  
Latitude: 43°07'35.92761"N Longitude: 123°03'04.19860"W