

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 15 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5532)

Set fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on N and S faces, from which
A hemlock, 6" dia., bears N.20°W., 6 lks., mkd: ¼ S BT.
A hemlock, 8" dia., bears S.40°W., 5 lks., mkd: ¼ S BT.

Adam DeGroot - For: Seneca Jones Timber Co - July 2017 - M173-46

At the proportioned position:
Set - A 1½"x30" iron post, 22" in the ground, in a 18" dia. x 6" high stone mound, with a 2½" brass cap marked:
T28S R3W
¼ . S15
2017
PLS 89398

New BTS- A 14" hemlock bears N.56°15'E., 23.5 ft scribed "¼ S15 BT"
A 22" hemlock bears N.42°W., 16.8 ft scribed "¼ S15 BT"

New reference monuments -
A MAG-HUB and brass washer set in low face notch of a 74" D.Fir bears S.66°47'W., 8.53 ft.
A MAG-HUB and brass washer set in opened face of a 37" D.Fir bears S.56°04'E., 56.11 ft.

NAD 83 STATION (2011) EPOCH 2010.00 GEODETIC COORDINATES:
Latitude: 43°07'35.52567"N Longitude: 123°02'29.84555"W