

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5547)

Set cedar post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N & S faces; from which

A fir, 14" dia., bears N.4°E., 53 lks., mkd: ¼ S BT.

A fir, 16" dia., bears S.16°W., 45 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-39

Found - Orig. 14" now 20" R.Fir N.4°E., 35.0 ft., shows good bark scribing.

Orig. SW BT now down.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS ¼ S 3 T28S R3W
OFFICE 1962 S 10

New BTs- 10" R.Fir bears N.60°W., 43.0 ft. scribed ¼ S3 CS BT

19" Laurel bears S.23°W., 49.6 ft. ¼ S10 CS BT

Note - Log road is 65 ft. north of ¼ corner.