

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6325)

-----

Set Laurel post for cor. to secs. 2, 3, 34 and 35, from which  
 A Cedar 48" dia., bears N.50°E., 70 lks.  
 A Laurel 20" dia., bears S.15°E., 38 lks.  
 A Cedar 15" dia., bears S.60°W., 35 lks.  
 A Fir 20" dia., bears N.62°W., 60 lks.

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5549)

-----

Sec. cor. for 2, 3, 34 and 35, which is a stake greatly decayed, marked and witnessed as described by the surveyor general. Set Cedar stake 3 ft. long, 6" sq., 24" in the ground for cor. secs. 2 and 3, marked T29S S2 on SE.; and R3W S3 on SW.; face, with 4 notches on E. and 2 notches on W. edge.  
 I destroy markings on bearing trees referring to secs. 34 and 35.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Stone; John Powell, crew - July 10-20, 1962 - C.S. File 52/126-23

-----

Found - Orig. 48" now 52" Cedar shows good scribing, N.50°E., 46.2 ft.  
 Orig. 15" now 28" Cedar S.62°W., 23.1 ft., shows good scribing.  
 Orig. 20" now 40" Fir N.54°W., 39.6 ft., not N.62°W., shows good bark scribing.

Set Brass cap at cor. mkd: County Surveyors Office

		T28S	R3W
		T29S	
S 3		S 2	1962

New BTs- 11" R.Fir bears S.29°E., 24.3 ft. scribed S2 T29S R3W CS BT.

Rescribed now 28" Cedar, S.56°W., 23.1 ft. S2 T29S R3W CS BT.

Corner is on West slope about 200 ft. West from top of ridge.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13798-99)

(Cont. Next Page)

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 444100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The Sec. cor., remonumented and recorded by Byron in 1962, with an iron post 1" dia., 12" above ground, firmly set, with brass cap mkd. in 1962, from which the original bearing trees:

A Cedar snag 50" dia., bears N.50°E., 70 lks. dist., mkd. T28S R3W BT on an open blaze.

A Madrone 23" dia., bears S.15°E., 42½ lks. dist., no marks visible on rotted blaze. (Rec. 38 lks.)

A Cedar 28" dia., bears S.64°W., 35 lks. dist., mkd. 29 R on original open blaze, remarked T29S R3W on open blaze alongside, and S3 T29S R3W CS BT on double blaze. (Rec. S.60°W.)

A Fir 38" dia., bears N.54°W., 60 lks. dist., mkd. S T28S R3W B on bark blaze. (Rec. N.62°W.)

and a bearing tree mkd. by Byron:

A Fir 12" dia., bears S.30°E., 37 lks. dist., with a partially healed double blaze.

Add the marks BLM to the brass cap.

Fd. OK by D. Edwards, Oct. 1999 - M133-43