TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5551)

Set granite stone 8x10x15", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 2 notches on E & 1 notch on S edge, from which

A fir, 5" dia. bears N.10°E., 40 lks. mkd: T28S R3W S26 BT
A fir, 14" dia. bears S.52°E. 12 lks. mkd: T28S R3W S35 BT
A fir, 5" dia. bears S.73°W., 27 lks. mkd: T28S R3W S34 BT
A cedar, 5" dia., bears N.44°W., 12 lks., mkd: T28S R3W S27 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Bill Stoffel - Aug. 8-10, 1962 - C.S. File 52/126-25

Found - Orig. 5" now 11" R.Fir N.11°E., 26.4 ft., shows scribing.
Orig. 14" now 24" R.Fir S.52°E. 7.9 ft., shows scribing.
Orig. 5" Fir S.73°W. 17.8 ft., dead, shows scribing.
Orig. 5", now 9" Cedar N.44°W. 7.9 ft, shows scribing.
We do not find Corner Stone.

Set Brass Cap at Corner Mkd County Surveyors S27|S26 T28S R3W Office, 1962 S34|S35

New BTs- 11" Cedar bears S.78°W. 17.5 ft. scribed S34 T28S R3W CS BT.