

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5558)  
-----  
Set stone 6x10x15", 10" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, and raise mound of stone 2 ft. base, 1½ ft. high W. of cor. from which  
A fir, 8" dia. bears S.47°E., 14 lks. mkd: T28S R3W S26 BT  
A fir, 8" dia. bears S.56°W., 47 lks. mkd: T28S R3W S27 BT  
A fir, 10" dia. bears N.55°W. 10 lks. mkd: T28S R3W S22 BT  
No other tree fit to mark.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Mike Stone - July 1962 - C.S. File 52/126-4  
-----  
Found - Stone at Corner as recorded & all BTs. SE BT shows scribing. SW BT is dead.  
Set - Brass Cap alongside Cor. Stone & mkd: County Surveyors  
T28S R3W S22|S23 Office, 1962  
                                  S27|S26  
New BTs- 27" R.Fir bears S.66°W. 40.3 ft.. scribed S26 T28S R3W CS BT.  
7" R.Fir bears N.10°E. 32.6 ft. scribed S25 CS BT.