

PRIMARY CORNER DESCRIPTION Corner Secs. 14 & 15, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5532-3)

Set cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 14, 15, 22, & 23, marked T28S S 14 on NE, R3W S 23 on SE, S 22 on SW, S 15 on NW faces, with 2 notches on E & 3 on S edges; from which
 A fir, 30" dia. bears N.50°E. 12 lks. mkd: T28S R3W S14 BT
 A cedar, 14" dia., bears S.45°E., 45 lks., mkd: T28S R3W S23 BT.
 A cedar, 24" dia., bears S.45°W., 15 lks., mkd: T28S R3W S22 BT.
 A fir, 24" dia. bears N.10°W. 66 lks. mkd: T28S R3W S15 BT

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol 13 Pages 5559-60)

Cor. of 14, 15, 22, & 23 which is a stake, marked & witnessed as described by the Surveyor general.....
 I destroy markings on cor. and BTs referring to secs. 22 & 23

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug./Sept. 1962 - C.S. File 52/126

Found - This corner was renewed by Strum. We find Orig N.E. N.W. & S.W. BTs.
 Find ¾" I.R. at corner.. -
 9" Hemlock N.16½°W., 31.0 ft. scribed RE 4287 S15 BT
 9" Hemlock S.22°W. 21.4 ft. scribed RE 4287 S22 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22292)

The cor. of secs. 14 and 15 only, perpetuated by person(s) unknown, reported by Byron, in 1962, monumented with a rebar, 36" long, ¾" dia., firmly set, projecting 7" above ground, from which the remains of an orig. bearing tree
 A hollow, decayed, sawed fir stump, size indeterminate, bears N.50°E., 7.9 ft., with no marks visible.
 and a BT mkd. by person(s) unknown, reported by Byron
 A hemlock, 14" dia., bears S.27¾°W., 20.9 ft., with a healed blaze.
 At the corner point
 Set a stainless steel post, 28" long, T28S R3W
 2½" dia., 27" in the ground, S 15|S 14
 with brass cap mkd. S 22
 2009

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Corner Secs. 14 & 15, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A fir, 11" dia., bears N.89¼°E., 16.9 ft., mkd. T28S R3W S14 BT.
A fir, 10" dia., bears N.16¼°W., 44.4 ft., mkd. T28S R3W S15 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
Place the rebar inside and deposit a magnet in a white plastic case at the base of the stainless steel post.
(CC Secs. 22 & 23 (North) bears S89°39'11"E., 111.91')

Adam DeGroot - For: Seneca Jones Timber Co. - July 2017 - M173-46

Found a 2½" stainless steel post by Kenneth Saveland in 2009 per USBLM Plat No. 7481, dated 03/24/2011 (DCSO Vol 56 Pg 22292), projecting 4" above ground, with a properly marked 3 1/4" brass cap and accessories per the 2009 BLM record.
NAD 83 STATION (2011) EPOCH 2010.00 GEODETIC COORDINATES:
Latitude: 43°07'35.14037"N Longitude: 123°01'54.30530"W