TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5540)

Set laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 10, 11, 14, & 15, marked T28S S 11 on NE, R3W S 14 on SE, S 15 on SW, S 10 on NW faces, with 2 notches on E & 4 notches on S edges; from which

A laurel, 8" dia., bears N.15°E., 32 lks., mkd: T28S R3W S11 BT.
A laurel, 7" dia., bears S.75°E., 23 lks., mkd: T28S R3W S14 BT.
A fir, 20" dia. bears S.65°W. 54 lks. mkd: T28S R3W S15 BT
A fir, 36" dia. bears N.45°W. 17 lks. mkd: T28S R3W S10 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug./Sept. 1962 - C.S. File 52/126-29

Found - Orig. 20" now 36" Fir S.65°W., 35.7 ft. shows good bark scribing.
Orig. 36" now 39" Fir N.45°W., 11.2 ft. no scribing found.
Orig. 8" now 12" Laurel N.15°E., 21.1 ft. face rotted no scribing.
Orig. SE BT not found.

Note - Corner is just off the west edge of log. road on top of ridge.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962

S10	S11
S15	S14

T28S R3W

New BTs- 11" laurel bears N.7°E., 18.8 ft. scribed S11 T28S R3W CS BT.
39" R.Fir (OBT) bears N.45°W., 13.2 ft. scribed S10 T28S R3W CS BT.
7" Dbl. R.Fir S.63°E., 43.8 ft. scribed S14 CS BT.