

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCS0 records Vol. 13 Page(s) 5541)

Set laurel post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on E & W faces; from which
 A fir, 40" dia., bears N.71°W., 14 lks., mkd: 1/4 S BT.
 A hemlock, 8" dia., bears N.69°E., 24 lks., mkd: 1/4 S BT.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1963 - C.S. File 51/254-14

Found - 3/4" iron rod - iron rod was set by me from orig. BTs in 1957. Subs. logging destroyed all BTs. I now replace iron rod with 2 1/2" alum cap & reference.
Set - 2 1/2" Alum. cap
 14" Cedar, S.31°W., 25.9 ft. mkd: 1/4 S10 BT.
 28" D.Fir stump N.23°E., 41.5 ft. mkd: 1/4 S11 BT.