

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5541-2)

-----

Set laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10, & 11, marked T28S S 2 on NE, R3W S 11 on SE, S 10 on SW, S 3 on NW faces, with 2 notches on E & 5 on S edges; from which

- A fir, 16" dia. bears N.22°E., 22 lks. mkd: T28S R3W S2 BT
- A fir, 16" dia. bears S.80°E. 26 lks. mkd: T28S R3W S11 BT
- A fir, 14" dia. bears S.25°W. 50 lks. mkd: T28S R3W S10 BT
- A fir, 14" dia. bears N.65°W., 45 lks. mkd: T28S R3W S3 BT

NOT FOUND

Shown as not found on the previous corner renewal index sheet  
Could find no record of visit but most likely DCSO in 1960's