

PRIMARY CORNER DESCRIPTION CC Secs. 22 & 23, North

Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5560)

Set granite stone, 6x10x15" 10" in the ground for closing cor. secs. 22 & 23, marked CC on S face, with 2 grooves on E & 4 grooves on W face, from which
 A hemlock, 18" dia., bears S.77°E., 57 lks., mkd: T28S R3W S23 BT.
 A cedar, 6" dia., bears S.74°E., 19 lks., mkd: T28S R3W S22 BT.
(CC lies S.89°41'W., 1.66 chains of the Corner of Sections 14 & 15 (South) page 5559)

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Found - Stone 6"x10"x15"
 26" hemlock, S.38°E., 39.0 ft.
Set - 3/4"x36" iron rod.
 10" hemlock S.37°W., 30.4 ft.
 60" fir N.18°E., 81.5 ft. (stump)

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug./Sept. 1962 - C.S. File 52/126

Found - BTs & rod at corner as recorded by Shrum, except NE BT, now stump, shows scribing.
New BT - 18" Hemlock bears S.31°E., 32.1 ft. scribed S23 T28S R3W CS BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22293)

The closing cor. of secs. 22 & 23, perpetuated by Shrum, Jr., in 1960, further perpetuated by Byron, in 1962, monumented with a rebar, 36" long, 3/4" dia., firmly set, projecting 8" above ground (alongside of which is the orig. basalt stone, 6x10x15", lying loose on the ground, with faint marks CC visible and 2 grooves on a face and 4 grooves on the opposite face), from which the remains of the orig. bearing trees
 A decayed, sawed hemlock stump, size indeterminate, bears S.77°E., 37.6 ft., with no marks visible on an open, decayed blaze.
 A roothole bears S.74°W., 12.5 ft., downhill of which is an uprooted, cedar snag, 13" dia., with no marks visible on an open, decayed blaze. (Record S.74°E.)
continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 502400

PRIMARY CORNER DESCRIPTION CC Secs. 22 & 23, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Shrum, Jr.
A sawed fir stump, 60" dia., bears N.17°E., 80.0 ft., with no marks visible.

A hemlock snag, 15" dia bears S.36¼°W. 30.2 ft with scribe marks S22 4287 visible on a partially healed blaze

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with brass cap mkd.

T28S R3W
S 14
S 22 | S 23
C C
2009

from which new bearing trees

A fir, 10" dia., bears S.17¼°E., 10.4 ft., mkd. T28S R3W S23 BT.

A cedar, 23" dia., bears S.42½°W., 19.1 ft., mkd. T28S R3W S22 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Place the rebar inside, bury the orig. stone alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.

(CC Secs. 14 & 15 (south) bears N.89°39'11"W., 111.91')

Adam DeGroot - For: Seneca Jones Timber Co. - July 2017 - M173-46

Found a 2 1/2" stainless steel post by Kenneth Saveland in 2009 per USBLM Plat No. 7481, dated 03/24/2011 (DCSO Vol 56 Pg 22293), projecting 2" above ground, with a properly marked 3 1/4" brass cap and accessories per the 2009 BLM record.
NAD 83 STATION (2011) EPOCH 2010.00 GEODETIC COORDINATES:
Latitude: 43°07'35.10208"N Longitude: 123°01'52.79627"W