

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 504100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 2 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCS0 records Vol. 15 Page(s) 6325)

Set Laurel post for 1/4 sec. cor., from which
A Fir 40" dia., bears South, 8 lks.
A Laurel 8" dia., bears N.10°E., 36 lks.

GL0 resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCS0 records Vol. 13 Page(s) 5549)

1/4 sec. cor. which is a stake greatly decayed, marked and witnessed as described by the surveyor general. Set Fir stake 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., marked 1/4 on S. face.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Feb. 2, 1960 - C.S. 49/47-12

Found - Fir stump now 40", South 5.3 ft. with old bark scribe, "1/4S" "B" showing.
No trace of other BT found.

At corner, Set Iron pipe with brass cap mkd: County Surveyors Office
T28S R3W
N 1/4 Cor. S2
T29S R3W
1960

Blaze and scribe new trees:
34" I.Cedar S.63°E., 7.5 ft. "N1/4 S2 CS BT"
30" I.Cedar S.2°W., 43.3 ft. "N1/4 S2 CS BT"

BLM resurvey by James J. Carlson, Cadastral Surveyor, under Group #892, surveyed June/July 1976 - (DCS0 records Vol. 39 Page(s) 15846)

The 1/4 sec. cor. of sec. 2 only, perpetuated by Byron in 1960, monumented with an iron post 1" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1960, from which the remains of the original bearing trees

A sawed Fir stump 40" dia., bears South 8 lks. dist., with scribe marks 1/4 S visible on bark.

and the remains of bearing trees mkd. by Byron:

A Cedar 35" dia., bears S.63°E., 12 lks. dist., with scribe marks N 1/4 S2 CS BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 504100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 2 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar snag 35" dia., bears S.2°W., 65½ lks. dist., with scribe marks N ¼ S2 CS BT.
and a new bearing tree:
A Fir 8" dia., bears S.1°W., 59 lks. dist., mkd. ¼ S2 BT.

David Edwards - For: Seneca Jones Timber Co. - 10/1999 - M133-43

Found - DCS0 brass cap
New BT - An 11" dia., Fir bears S.41°E., 21.42 ft.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 9/18/2018 (filed 11/10/2021) - C.S. File 67/49-21

Found - A 1" dia., iron pipe, leaning west (reference out and returned to firm plum position projecting 8" above ground.) by Byron in 1960, with a 2½" brass cap (properly) marked
An original bearing tree by W.H. Byars in 1881 -
A 34"x3' tall D.Fir stump bears South, 6.6 ft. with a healed blaze. (Rec. 8 lks. to face)
A BT by J. Byron in 1960 -
A 30"x6' tall cedar snag bears S.63°E., 7.92 ft. with a healed blaze. (Rec. 7.5 ft)
A BT by J. Carlson, in 1976 -
A 15"x2½' tall D.Fir stump bears S.1°W.. 38.9 ft with a healed blaze.
A BT by D. Edwards in 1999 -
A 12" D.Fir (top dead) bears S.41°E., 21.8 ft. with scribe marks vis. on a partially healed blaze. Rec. 21.42 ft.)
New - A 4" hemlock bears S.6°W., 20.1 ft. scribed "X"."CSBT"
A 14"x1.6' D.Fir stump bears S.71½°W., 10.6 ft. to a 8" galv. spike driven in the center of the stump.
A 6' metal post hears West. 1.6 ft.
Note - All BTs have BT tags attached. All new BTs have double blazed faces with hearings measured to the center of the tree at the root crown and distances measured to a 2½" PK nail in the side and center of the root crown.
Geodetic coordinates
Lat: 45°05'03.411454105 N. Long: 123°01'49.491026670 W.
Compass declination: 15°E

continued next page

2

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 504100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 2 only, T29-3

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____