

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 23

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Set - 3/4"x36" Iron rod.
21" Fir, S.16°E., 18.4 ft.
13" Fir, N.6°30'E., 14.2 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22305)

The center 1/4 sec. cor. of sec. 23, established by Shrum, Jr., in 1960, and is accepted as the cor., monumented with a rebar, 36" long, 3/4" dia., firmly set, bent N., projecting 8" above ground, from which the remains of BTs mkd. by Shrum, Jr

A roothole bears N.17 1/2°E., 15.2 ft.
A sawed fir stump, 25" dia., bears S.15°E., 17.9 ft., with a healed double blaze.

At the corner point
Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd.

T28S R3W
C 1/4 S 23
2009

from which new bearing trees

A fir, 6" dia., bears S.9°E., 11.3 ft., mkd. X BT.
A fir, 15" dia., bears S.87 1/4°W., 42.8 ft., mkd. C 1/4 S23 BT.

Place the rebar inside and deposit a magnet in a white plastic case at the base of the stainless steel post.

From the cor., N.0°10'00"E., at:
170 ft., creek, 3 ft. wide, course N.25°W.

From the cor., S.89°41'57"E., at:
135 ft., creek, 3 ft. wide, course N.50°W.

1