

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5542-3)

Set yew post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked on N & S faces ¼ S; from which
 A fir, 30" dia., bears N.27°E., 17 lks., mkd: ¼ S BT.
 A cedar, 36" dia., bears S.5°E., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-39

Found - Orig. 36" now 46" cedar S.5°E., 6.6 ft. We open & find good scribing.
 Orig. NE BT now down & rotted.
 Also find ¾" IR at corner.
New BTs- 10" Hemlock bears S.22°E., 3.0 ft. scribed ¼ S11 CS BT.
 14" Cedar bears N W 8.9 ft. scribed ¼ S2 CS BT.
Note - No bearing given for NW BT in renewal per research 2/26/2009 DCSO JC