

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 542400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 23 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Set - 3/4"x36" iron rod.
12" hemlock S.27°W., 38.3 ft.
12" hemlock S.14°30'E., 38.0 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22295)

Point for the 1/4 sec. cor. of sec. 23 only, established by Shrum, Jr., Registered Engineer No. 4287, in 1960, reestablished at proportionate distance utilizing the 1960 Shrum survey; there is no remaining evidence of the Shrum cor. position.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd.

T28S R3W
1/4 S 23
2009

from which

A fir, 11" dia., bears S.77 1/2°E., 6.9 ft., mkd. X BT.

A fir, 11" dia., bears S.45 1/2°W., 26.2 ft., mkd. 1/4 S23 BT.

Each new bearing tree has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

S 1/4 corner Sec. 14 only bears S.89°52'48"W., 96.57'