

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5550)

Set granite stone 6x10x14", 10" in the ground for cor. of secs. 25, 26, 35, & 36 mkd with 1 notch on S & E edges, from which

A cedar, 12" dia., bears N.32°E., 32 lks., mkd: T28S R3W S25 BT.

A fir, 14" dia. bears S.63°E. 55 lks. mkd: T28S R3W S36 BT

A laurel, 12" dia., bears S.88°W., 17 lks., mkd: T28S R3W S35 BT.

A fir, 12" dia. bears N.24°W. 10 lks. mkd: T28S R3W S26 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Mike Stone - July 1962 - C.S. File 52/126-4

Found - All BTs as recorded.
SW BT shows good scribing.
We also find corner stone.

Set - Brass cap alongside corner stone & mkd:
COUNTY SURVEYORS OFFICE 1962
T28S R3W S 26|S 25
S 35|S 36

No new BTs scribed.
Note - Forest Road bears north 40 ft.