

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5553-4)

Set granite stone 6x10x14", 10" in the ground for cor. of secs. 23, 24, 25, & 26 mkd with 1 notch on E & 2 notches on S edges, from which
 A yew, 10" dia. bears N.50°E., 6 lks. mkd: T28S R3W S24 BT
 A hemlock, 12" dia., bears S.14°E., 23 lks., mkd: T28S R3W S25 BT.
 A hemlock, 6" dia., bears S.50°W., 57 lks., mkd: T28S R3W S26 BT.
 A cedar, 24" dia., bears N.72°W., 51 lks., mkd: T28S R3W S23 BT.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Found - 6"x10"x14" stone.
 26" hemlock - S.14°E., 15.2 ft.
 12" hemlock - S.49°W., 37.0 ft.
Set - ¾" x 36" iron rod.
 6" hemlock - N.43°E., 27.4 ft.

Victor McLind, LS #934 - For: Umpqua National Forest - Sept. 1978 - M70-36

Found - ¾" I.R. with orig. stone alongside from which:
 30" Hemlock bears S.22°30'E., 15.2 ft. face with scribing visible.
 40" cedar bears N.70°W., 33.8 ft. face with scribing visible.
 SW and NE BT's are down.
Set - 2"x30" Galv. IP with 3" brass cap stamped T28S R3W S23 S24 S26 S25 RLS 934 1978.
New BTs- 26" Cedar bears S.44°30'W., 71.6 ft. I blazed & scribed T28S R3W S26 BT"
 8" Hemlock bears N.45°E., 35.7 ft. I blazed & scribed "T28S R3W S24 BT"
Set - ¾" Iron rod and stone alongside new monument.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22300)

The cor. of secs. 23, 24, 25, and 26, perpetuated by McLind, in 1978, monumented with an iron post, 2½" dia., firmly set, projecting 6 ins. above ground, (alongside of which is the orig. basalt stone, (Record, granite) 6x10x14", cont.

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

loosely set, projecting 3" above ground, with 2 grooves visible on the S. face) with brass cap (properly) mkd. from which the remains of the orig. bearing trees

- A hemlock snag, 35" dia., bears S.26°E., 15.2 ft., with scribe marks T28S R3W S25 BT visible on a partially healed blaze. (Record, S.14°E.)
- A cedar, 45" dia., bears N.72°W., 33.7 ft., with scribe marks R3 S23 visible on a partially healed blaze.

and the remains of a bearing tree mkd. by McLind

- A roothole bears S.43°W., 70.6 ft., alongside of which is an uprooted, sawed cedar stump, 28" dia., with no marks visible.

and new bearing trees

- A fir, 7" dia. bears N.68°E. 37.3 ft. mkd. T28S R3W S24 BT
- A hemlock, 15" dia., bears S.59¼°E., 56.6 ft., mkd. T28S R3W S25 BT.
- A hemlock, 13" dia., bears S.5½°W., 14.3 ft., mkd. T28S R3W S26 BT.

Bury the orig. stone alongside the iron post.

From the cor., N.89°42'15"E., at:
20 ft., draw, drains N.20°E.

From the cor., N.0°01'11"W., at:
45 ft., gravel road, 12 ft. wide, bears N.80°W. & East, in curve.