

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5556)

Set stake, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S23 on W., & 24 on E face, from which:
A yew, 10" dia., bears N.79°E., 45 lks., mkd: ¼ S24 BT.
A fir, 40" dia., bears West, 20 lks., mkd: ¼ S23 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Found - 13" Yew - N.79°E., 31.2 ft.
56" Fir - West, 13.70 ft.
Set - ¾"x36" iron rod
12" Yew - N.48°W., 58.0 ft.
13" Yew - N.79°E., 31.2 ft. (Rescribed)

Victor McLind, LS #934 - For: Umpqua National Forest - Sept. 1978 - M70-36

Found - ¾" Iron rod, 1960, from which
14" yew stump bears N.47°W., 57.8 ft. lower face with scribing "BT" visible.
14" Yew bears N.82°E., 31.2 ft. face with scribing visible.
56" fir stump bears N.84°W., 15.5 ft. No scribing visible.
Set - 2"x30" galv. IP with 3" brass cap stamped T28S R3W ¼ S23 S24 RLS 934 1978.
¾" IR alongside.

Gerald Nygren, LS 1035 - March 1988 - C.S. 63/69-13

Found - A 2" galv. iron pipe with 3" brass cap extending 7" above ground and a ¾" iron rod alongside. Brass cap is marked "T28S R3W ¼ S23 S24 RLS 934 1978"
14" Yew, bears N.82°E., 31.2 ft..(vis. scribing)
14" Yew stump, bears N.47°W, 57.8 ft. (vis. scribing)
56" fir stump, bears N.84°W, 15.5 ft.
Set- 5" D.Fir, bears S.30°W, 17.8 ft. scribed "X"BT"
A 1/2" washer marked "RLS 1035" was nailed flush to the lower blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22302)

The ¼ sec. cor. of secs. 23 & 24, perpetuated by Shrum, Jr., in 1960, subsequently perpetuated by McLind, in 1978, and further perpetuated by Nygren, in 1988, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A sawed yew stump, 14" dia., bears N.79°E., 29.7 ft., with scribe marks RE 428/ BT visible on an open blaze, alongside of which is a down yew, with scribe marks ¼ S24 visible on a partially healed blaze. (Rescribed by Shrum, Jr.)

A sawed fir stump, 56" dia., bears West, 13.2 ft., with no marks visible on an opened blaze.

and the remains of a bearing tree mkd. by Shrum, Jr.

A sawed, decayed yew stump, 12" dia., bears N.48½°W., 57.7 ft., with scribe marks BT visible on a partially healed blaze, alongside of which is a down yew, with no marks visible.

and a bearing tree mkd. by Nygren

A fir, 12" dia., bears S.27°W., 17.9 ft., with a healed double blaze.

and a new bearing tree

A hemlock, 5" dia., bears S.85½°E., 10.2 ft., mkd. X BT.

Corner is located on a gentle NE. slope.

From the cor., S.0°01'14"W., at:

205 ft., creek, 3 ft. wide, course S.80°E.