

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 14 (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5533-4)

Set cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23, & 24, marked T28S S 13 on NE, R3W S 24 on SE, S 23 on SW, S 14 on NW faces, with 1 notch on E & 3 on S edges; from which
A fir, 36" dia. bears N.34°E. 49 lks. mkd: T28S R3W S13 BT
A fir, 36" dia. bears S.55°E. 63 lks. mkd: T28S R3W S24 BT
A fir, 40" dia. bears S.35°E. 55 lks. mkd: T28S R3W S23 BT
A fir, 30" dia. bears N.64°W. 65 lks. mkd: T28S R3W S14 BT

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5555-6)

Cor. secs. 13, 14, 23, & 24
Set stone, 6x12x14", 10" in the ground for cor. secs. 13 & 14, marked with 5 notches on W & 1 notch on E edge.
I destroy markings on BTs referring to secs. 23 & 24.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Found - 6"x12"x14" stone.
36" hemlock - N.64°W., - 42.9 ft. (stump)
42" fir - N.34°E., - 32.3 ft. (stump)
42" fir - S.55°E., - 41.6 ft. (stump)
Set - 3/4" x 36" iron rod.
42" fir, N.15°30'E., 32.6 ft. (stump)
36" hemlock, N.66°W., 42.6 ft. (stump)
8" yew, S.12°E., 96.0 ft.

Dennis Gaylord, USFS & Deputy Douglas Co. Surveyors Office -
Witness: Randall Lopez - May 25, 1978 - C.S. File 60/11-12

Found - 2½" alum. cap on a 1" IR cap is 10" above ground surface & firmly set. Orig. corner stone is lying alongside. Stone is marked with 2 notches on one face & one notch on a face 90° from previous notched face.
36" Hemlock stump bears N.67°W., 42.6 ft. scribing visible "S14 RE428T BT"
42" Fir stump bears N.15°30'E., 32.6' scribing visible "S13 RE428T"
42" Fir stump bears N.37°E., 32.8' no scribing or healed blazes visible.
42" D.Fir stump bears S.55°E., 44.2' no scribing or healed blazes visible. continued next pg

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 14 (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

18" yew snag bears S.12°15'E., 96.0 ft. scribing visible, "S23 RE 28T BT"
New - 5" D.Fir bears N.14°45'W., 46.2' scribed "X BT" on a double blaze.
5" D.Fir bears S.62°W., 73.7' scribed "X BT" on a double blaze.
Note - No other trees of sufficient size available.
Corner lies 100' South of FS Rd. #2806 in clearcut.

Gerald Nygren, LS 1035 - March 1988 - C.S. 63/69-15

Found - A 3/4" iron pipe with 2 1/2" alum, cap ext. 12" above ground & mkd USPC PROP COR T28S R3W 14|13 RE 4287
23
9" D.Fir, bears N.14°45'W., 46.2 ft. Blaze healed.
9" D.Fir, bears S.62°W., 73.7 ft. Blaze healed.
18" Yew (dead), bears S.12 3/4°E., 96.0 ft. Vis. scribe.
42" fir stump, bears N.37°E, 32.8 ft.
42" fir stump, bears N.15 1/2°E, 32.6 ft. Vis. scribe.
36" Hemlock (rotted) stump, bears N.67°W, 42.6 ft.
Set - 6" D.Fir, bears N.73°E, 38.0 ft., scribed "S13 T28S R3W BT" with brass washer stamped "RLS 1035"
Nailed flush with the lower end of the blaze.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22296)

The cor. of secs. 13 & 14 only, perpetuated by Shrum, Jr., in 1960, subsequently perpetuated by Gaylord, in 1978, and further perpetuated by Nygren, in 1988, monumented with an iron post, 1" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A sawed fir stump, 48" dia., bears N.34°E., 32.3 ft., with no marks visible.
A decayed hemlock stump, size indeterminate, bears N.67 1/2°W., 41.4 ft., with no marks visible.
and the remains of bearing trees mkd. by Shrum, Jr.
A sawed fir stump, 42" dia., bears N.15 1/4°E., 32.2 ft., with axe marks visible on an opened blaze.
A burnt yew snag, 11" dia., bears S.12 1/2°E., 95.8 ft., with scribe marks S23 RE 4287 visible on an open blaze.
and bearing trees mkd. by Gaylord
A fir, 14" dia., bears S.62°W., 73.8 ft., with a healed double blaze.
A fir, 16" dia., bears N.14 1/4°W., 46.1 ft., with a healed double blaze.
continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 14 (South)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and a bearing tree mkd. by Nygren
A fir, 11" dia., bears N.71¼°E., 38.2 ft., with a healed
blaze.
CC Secs. 23 & 24 (North) bears N.88°20'03"E., 74.00'