

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5535)

Set fir post, 4 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on E & W faces; from which
A cedar, 30" dia., bears N.54°W., 39 lks., mkd: ¼ S BT.
A cedar, 6" dia., bears S.35°E., 11 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm Stoffel - Sept. 1962 - C.S. File 52/126-50

Found - Orig. 30" now 40" Cedar stump N.54°W., 25.7 ft. shows axe on old face. No scribing found.
Orig. 6" now 14" Cedar S.35°E., 7.3 ft. shows old axe work, now stump.
Also find section of old pointed stake in place at corner.
Set - Brass cap at cor. & set cedar post alongside mkd:
COUNTY SURVEYORS OFFICE 1962 ¼ S14|S13 T28S R3W
Note - Log. road is about 100 ft. south of ¼ corner.
New BT - 10" Maple bears S.81°W. 128.6 ft scribed ¼ S14 CS BT
Rescribe 40" cedar stump N.54°W. 25.7 ft ¼ S14 CS BT