

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5535-6)  
-----  
Set Fir post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 11, 12, 13, & 14, marked T28S S 12 on NE, R1W S 13 on SE, S 14 on SW, S 11 on NW faces, with 1 notch on E & 4 notches on S edges; from which  
A fir, 30" dia. bears N.15°E. 42 lks. mkd: T28S R3W S12 BT  
A hemlock, 10" dia., bears S.25°E., 45 lks., mkd: T28S R3W S13 BT.  
A fir, 36" dia. bears S.20°W. 51 lks. mkd: T28S R3W S14 BT  
A maple, 8" dia., bears N.20°W., 58 lks., mkd: T28S R3W S11 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm Stoffel - Sept. 1962 - C.S. File 52/126-53  
-----  
Found - Orig. 8" maple, down, N.20°W., 38.3 ft.  
Orig. 36" fir, now dead, S.20°W., 33.7 ft.  
Orig. 10" now 17" hemlock S.29°E., not S.25°E., 25.7 ft., not 29.7 ft. shows scribing.  
Orig. 30" Fir, now dead, N.15°E., 21.7 ft. not 27.7 ft. shows scribing.  
Set Brass cap at cor. mkd: COUNTY SURVEYORS S 11|S 12 T28S R3W  
OFFICE 1962 S 14|S 13  
New BTs- 34" Cedar bears N.83°E., 24.3 ft. scribed S12 T28S R3W CS BT.  
8" hemlock bears N.5°W., 32.2 ft. S11 T28S R3W CS BT  
9" hemlock bears S.49°W., 49.0 ft. scribed S14 T28S R3W CS BT.